

APRICOT 2013


Singapore

19 February - 1 March 2013




ISP and NSP Security Workshop


APRICOT 2013



Source based RTBH


S/RTBH






Destination Based RTBH

- Requires knowledge of the target (victim) address/network.
- Willingly sacrifices (black-holes) the communication of the target with the rest of the world.
- Relies on BGP to “signal” black-hole from trigger to one or more enforcers – usually edge routers in the network.
- Uses unreachable next-hop to drop packets to the destination




Source Based RTBH

- Requires knowledge of the attack sources
- Attack sources are unable to communicate with the entire protected infrastructure, not only the intended victims.
- Relies on BGP to “signal” black-hole from trigger to one or more enforcers- usually edge routers in the network.
- Uses Unicast Reverse Path Forwarding(uRPF) to drop packets.



PE Configuration


- Configure the Loopback-11 with the ip address.
- 11.11.11.11 255.255.255.255
- Eg.
 - PE(config)# interface loopback11
 - PE(config-if)#ip address 11.11.11.11 255.255.255.255



Announced the loopback-11 via BGP

Eg. Router bgp <ASN>

```
PE(config-router)network 11.11.11.11 mask  
255.255.255.255
```



CE Configuration

- remove the community from 100.0.<router-id>.1/32 and add the trigger for 11.11.11.11/32.
- Add the route-map
ip community-list standard RTBH-Trigger permit 666:666

```
route-map RTBH-Trigger permit 10  
match tag 666  
set community 666:666
```

```
!
```


```
route-map RTBH-Trigger permit 99
```

```
!
```

```
route-map UseRTBH permit 10  
match community RTBH-Trigger  
set ip next-hop 192.0.2.1
```

```
!
```

```
route-map UseRTBH permit 99
```



CE Configuration

Eg.

CE-router#

```
router bgp <ASN>
```


```
no network 100.0.X.1 mask 255.255.255.255 route-map  
Loopback2-RTBH
```

```
network 100.0.X.1 mask 255.255.255.255
```

```
redistribute static route-map RTBH-Trigger
```

!

```
ip route 11.11.11.11 255.255.255.255 Null0 tag 666
```



Check the Victim Source

```
PE#sh ip bgp 11.11.11.11
```

```
BGP routing table entry for 11.11.11.11/32, version 25
```

```
Paths: (2 available, best #2, table Default-IP-Routing-Table)
```

```
Advertised to update-groups:
```

```
1      2
```

```
81
```

```
192.0.2.1 from 10.0.18.6 (192.168.31.1)
```


```
Origin incomplete, metric 0, localpref 100, valid, external
```

```
Community: 666:666
```

```
Local
```

```
0.0.0.0 from 0.0.0.0 (10.0.18.251)
```

```
Orig
```



Ping with Source loopback11 from PE

```
PE#ping 100.0.X.1 source lo11
```


```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 100.0.X.1, timeout is 2  
seconds:
```

```
Packet sent with a source address of 11.11.11.11
```

```
.....
```

```
Success rate is 0 percent (0/5)
```



Ping with Source loopback0 from PE

```
PE#ping 100.0.X.1 source lo0
```

```
Type escape sequence to abort.
```


```
Sending 5, 100-byte ICMP Echos to 100.0.X.1, timeout is 2 seconds:
```

```
Packet sent with a source address of 10.0.18.251
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 12/101/232 ms
```

```
PE#
```




Debug on CE and re-run the ping.

CE:

```
access-list 100 permit icmp any any echo
```

```
access-list 100 permit icmp any any echo-reply
```

```
CE-Router#debug ip packet 100
```



PE#ping 100.0.X.1 source lo11 repeat 1

Type escape sequence to abort.

Sending 1, 100-byte ICMP Echos to 100.0.X.1, timeout is 2 seconds:

Packet sent with a source address of 11.11.11.11

.

Success rate is 0 percent (0/1)

PE#

CE#debug ip packet 100

IP packet debugging is on for access list 100

Router31#


*Feb 21 12:37:14.959: IP: tableid=0, s=11.11.11.11 (Ethernet1/0), d=100.0.X.1 (Loopback2),
routed via RIB

*Feb 21 12:37:14.959: IP: s=11.11.11.11 (Ethernet1/0), d=100.0.X.1, len 100, rcvd 4

*Feb 21 12:37:14.963: IP: tableid=0, s=100.0.X.1 (local), d=11.11.11.11 (Null0), routed via RIB


*Feb 21 12:37:14.967: IP: s=100.0.X.1 (local), d=11.11.11.11 (Null0), len 100, sending

CE#



Use uRPF

```
PE
interface Ethernet X/X
description Link to CE-X e X/X
ip address X.X.X.Y 255.255.255.252
ip verify unicast source reachable-via any
```



PE#ping 100.0.X.1 source lo11 repeat 1

Type escape sequence to abort.

Sending 1, 100-byte ICMP Echos to 100.0.X.1, timeout is 2 seconds:

Packet sent with a source address of 11.11.11.11

·
Success rate is 0 percent (0/1)

PE#